Gekko-60

Datasheet



The Gekko-60 is recognized worldwide as one of the best GPR-antennas when maximum penetration is required. It is a UWB VHF GPR portable lightweight antenna with very high penetration. This antenna, with its good penetration and signal to noise ratio, is an example of the fact that deep penetration and good resolution can be achieved at once. It is therefore ideal for applications that require deep penetration and high resolution, while still having an easily maneuverable GPR system. Examples of such applications are water level mapping, dam structural integrity surveys and more.

The precise design of the outer shell of Gekko-60 provides a stable construction that doesn't tip and withstands the challenges that will be presented by the outer environment.

Gekko-60 is fully compatible with the rest of the Geoscanners equipment. It is easily mounted on the GST-806 cart, designed specifically to be used on cars or other vehicles, or with the SVC-820 cart(standard 4 wheel cart).

Just as with the rest of the Geoscanners antennas, Gekko-60 is designed with the end user in mind. It can be used in both monostatic mode or in bistatic mode. Depending on which mode is desirable by the user, the antenna comes equipped with top of the line Geoscanners plug-in electronics; TR-501 for monostatic mode or a combination of RX-501 and VHT-501 for bistatic mode. By including the transceivers in the antenna, we made sure that the end user receives a highly integrated device with all the matching already made to give the best possible results.







Mechanical and Environmental Specifications

Dimensions LxWxD (mm/inches) Weight (kg/pounds) Fastening points LxW (mm/inches) Ingress Protection*

Operating Temperature (°C / °F)**
Relative Humidity (%)

*TR501 attached

** Antenna only, for the electronics refer to the appropriate datasheet.

2045x155x215 / 80.51x6.1x8.46 5 / 11.02

260x60 / 10.23x2.36

IP54

from -25 to +40 /from 13 to +104

96 (NC)

Electrical Specifications

Antenna Type
Shield Type
Feed point impedance (Ohms)
Transmitted Pulse Amplitude (Volts)
Antenna Bandwidth (at 10dB)
Antenna Center Frequency (Mhz at 10dB BW)
Survey Wheel Output Voltage (Volts)

*** This data is proliminary based on limited amount of units

*** This data is preliminary based on limited amount of units

**** By using VHT501

Resistively loaded butterfly folded dipole

Unshielded 387*** 120 / 600**** 85.2%* 64.75 5.01

Recommended Specifications

Pulse repetition Frequency, PRF (kHz) ≤50 Scan Rate, Scans/Second ≤50

Range (ns), (depends on soil penetration) 150 - control unit maximum

Low Pass Filter Cut-Off Frequency (MHz) 25 High Pass Filter Cut-Off Frequency (MHz) 130

Gain Adjust to 75% Swing

Accessories*

- GST-806 Car survey trailer
- SVC-820 Standard 4 wheel cart
- K-100B Adapter for SVC820
- ASH-822 Hand carrier for one Gekko antenna

*Accessories are not included

Note: The information in this datasheet is based on the latest information at the time of publication. Geoscanners AB® reserves the right to make changes at any time, without notice to color, specifications, accessories, materials and models. For more information contact the Geoscanners AB Sales Department +46(0)92153020. ©2015 Geoscanners AB. Sweden.

Page 2 of 3 REV: EN161213-04



Terms of use

Geoscanners AB has made all reasonable efforts to ensure that all information provided through this document is accurate at the time of inclusion; however, there may be inadvertent and occasional errors for which Geoscanners AB apologizes.

Geoscanners AB accepts no liability for any inaccuracies or omissions in this document and any decisions based on information contained in this document are the sole responsibility of the reader. Geoscanners AB accepts no liability for any direct, special, indirect, or consequential damages, or any other damages of whatsoever kind, resulting from whatever cause through the use of any information obtained either directly or indirectly from this document.

This document may not be copied, reproduced, re-published, downloaded, posted, broadcast or transmitted in any way except for your own personal use. Any other use requires the prior written permission of Geoscanners AB. You agree not to adapt, alter or create a derivative work from any of the material contained in this document or use it for any other purpose other than for your personal use. You agree to use this document only for lawful purposes, and in a manner which does not infringe the rights of, or restrict or inhibit the use and enjoyment of this document by any third party.

This document and the information, names, images, pictures, logos and icons regarding or relating to Geoscanners AB, its products and services (or to third party products and services), is provided "AS IS" and on an "IS AVAILABLE" basis without any representation or endorsement made and without warranty of any kind whether express or implied, including but not limited to the implied warranties of satisfactory quality, fitness for a particular purpose, non-infringement, compatibility, security and accuracy.

In no event will Geoscanners AB be liable for any damages including, without limitation, indirect or consequential damages, or any damages whatsoever arising from use or loss of use, data, or profits, whether in action of contract, negligence or other tortuous action, arising out of or in connection with the use of this document. Geoscanners AB does not warrant that the functions contained in the material contained in this document will be uninterrupted or error free, that defects will be corrected. The names, images and logos identifying Geoscanners AB and their products and services are proprietary marks of Geoscanners AB. Nothing contained herein shall be construed as conferring by implication or otherwise any license or right under any trade mark or patent of Geoscanners AB, or any other third party.

If there is any conflict between these Terms and Conditions and rules and/or specific terms of use appearing in this document relating to specific material then the latter shall prevail.

If any of these Terms and Conditions should be determined to be illegal, invalid or otherwise unenforceable by reason of the laws of any state or country in which these Terms and Conditions are intended to be effective, then to the extent and within the jurisdiction which that Term or Condition is illegal, invalid or unenforceable, it shall be severed and deleted from this clause and the remaining terms and conditions shall survive, remain in full force and effect and continue to be binding and enforceable.

These Terms and Conditions shall be governed by and construed in accordance with the laws of Sweden. Disputes arising here from shall be exclusively subject to the jurisdiction of the courts of Sweden.

If these Terms and Conditions are not accepted in full, the use of this document must be terminated immediately.

Page 3 of 3 REV: EN161213-04